

MY19 ROCKSHOX TECHNICAL SPECIFICATION OVERVIEW

Wheel size	Category	Fork	Travel (MM)	Axle to crown at max travel	Offset (MM)	Upper tube diameter (MM)	Steerer length/ Taper length		Hub fitment						Max tire (MM)		Rotor Size (MM)		Remote compatibility	
							1-1/8"	Tapered	QR	15x100	15x110 Boost	Predictive Steering	15x150	20x110 Boost	Max diameter	Max width	Max	Min		
26"	XC	Bluto	80/100/120	531	51	32		265/85							STD	760	116	220	160	TwistLoc, OneLoc
		30 Gold	80/100	473	40	30	265		QR							680	58	220	160	TwistLoc, OneLoc
		30 Silver	80/100	475	40	30	265	265/80	QR							680	58	220	160	PopLoc
	Gravity	Pike DJ	100/140	522	40	35		265/85								694	66	220	160	Crown only
27.5"	XC	Reba (100)	100	487	42	32		245/85			TC/STD					714	62	220	160	TwistLoc, OneLoc
		Recon Gold (120)	80/100/120	509	42	32		265/85			STD					714	62	220	160	TwistLoc, OneLoc
		Recon RL (120)	80/100/120	506	42	32	265	265/85	QR		STD					710	62	220	160	TwistLoc, OneLoc
		Recon TK	80/100	486	42	32	265	265/85	QR		STD					710	62	220	160	PopLoc
		30 Gold	80/100/120	508	42	30	265	265/85	QR							710	62	220	160	TwistLoc, OneLoc
		30 Silver	80/100/120	510	42	30	265	265/85	QR							710	62	220	160	PopLoc
			XC 30	80/100/120	510	42	30	265	265/85	QR						710	62	220	160	PopLoc
		Trail	RS-1	100/120/130	517	42	32		265/85						PS	710	62	220	160	TwistLoc, OneLoc
	Reba (150)		130/140/150	537	42	32		265/85			STD					717	62	220	160	TwistLoc, OneLoc
	Reba (120)		120	507	42	32		265/85			STD					710	62	220	160	TwistLoc, OneLoc
	Recon Gold (130)		130	519	42	32		265/85			STD					714	62	220	160	TwistLoc, OneLoc
	Recon RL (140)		130/140	530	42	32		265/85			STD					717	62	220	160	TwistLoc, OneLoc
27.5" B	XC	SID	100	487	42	32		245/85			TC/STD				714	81	220	160	TwistLoc, OneLoc	
		Reba (100)	100	487	42	32		245/85			TC/STD				714	81	220	160	TwistLoc, OneLoc	
		NEW SEKTOR (120)	80/100/120	514	46	32		265/85			TC/STD				732	81	220	160	TwistLoc, OneLoc	
		Recon RL (120)	80/100/120	510	42	32		265/85			TC/STD				717	81	220	160	TwistLoc, OneLoc	
		Judy Gold	80/100/120	512	42/51	30		265/85			TC/STD				732	81	220	160	TwistLoc, OneLoc	
		Judy Silver	80/100/120	510	42/51	30		265/85			TC/STD				732	81	220	160	PopLoc	
		Trail	Revelation	120/130/140/150/160	552	37/46	35		245/85			TC/STD				732	81	220	180	TwistLoc, OneLoc
	Reba (150)		130/140/150	537	42	32		265/85			TC/STD				714	81	220	160	TwistLoc, OneLoc	
	Reba (120)		110/120	507	42	32		265/85			TC/STD				712	81	220	160	TwistLoc, OneLoc	
	NEW SEKTOR (150)		130/140/150	544	46	32		265/85			TC/STD				732	81	220	160	TwistLoc, OneLoc	
	Recon RL (150)		130/140/150	540	42	32		265/85			TC/STD				717	81	220	160	TwistLoc, OneLoc	
		Enduro	Lyrik	150/160/170/180	572	37/46	35		265/85			TC/STD				732	81	220	180	TwistLoc, OneLoc
	Pike		120/130/140/150/160	552	37/46	35		245/85			TC/STD				732	81	220	180	TwistLoc, OneLoc	
	Yari		150/160/170/180	572	37/46	35		265/85			TC/STD				732	81	220	180	Crown only	
		Gravity	NEW BoXXer	200	581	48	35	268							STD	732	81	220	200	Crown only

*All measurements in MM

MY19 ROCKSHOX TECHNICAL SPECIFICATION OVERVIEW

Wheel size	Category	Fork	Travel (MM)	Axle to crown at max travel	Offset (MM)	Upper tube diameter (MM)	Steerer length/ Taper length		Hub fitment					Max tire (MM)		Rotor Size (MM)		Remote compatibility	Brake Option		Other Compatibilities
							1-1/8"	Tapered	QR	15x100	15x110 Boost	Predictive Steering	15x150	20x110 Boost	Max diameter	Max width	Max		Min	Rim	
29"	XC	RS-1	100/120	526	51	32		265/90							751	62	220	160	TwistLoc, OneLoc		
		Reba (100)	100	506	51	32		245/85							755	62	220	160	TwistLoc, OneLoc		
		Recon Gold (120)	80/100/120	528	46/51	32		265/85			TC/STD				755	62	220	160	TwistLoc, OneLoc		
		Recon RL (100)	80/100	505	46/51	32		265/85			QR	STD			755	62	220	160	TwistLoc, OneLoc		
		Recon TK	80/100	505	46/51	32		265/85			QR	STD			755	62	220	160	PopLoc		
		30 Gold	80/100/120	527	46/51	30		265/85			QR				755	62	220	160	TwistLoc, OneLoc		
		30 Silver	80/100	509	46/51	30		265/85			QR				755	62	220	160	PopLoc		
	XC 30	80/100	509	46/51	30		265/85			QR				755	62	220	160	PopLoc			
	Trail	Reba (150)	130/140/150	556	51	32		265/85				STD			755	62	220	160	TwistLoc, OneLoc		
		Reba (120)	120	526	51	32		265/85				STD			755	62	220	160	TwistLoc, OneLoc		
Recon Gold (130)		130	538	46/51	32		265/85				STD			755	62	220	160	TwistLoc, OneLoc			
Recon RL (140)		120/130/140	549	46/51	32		265/85				STD			755	62	220	160	TwistLoc, OneLoc			
29" B	XC	SID (100)	100	506	51	32		245/85						755	81	220	160	TwistLoc, OneLoc			
		NEW SID (120)	110/120	531	51	32		245/85						760	81	220	160	TwistLoc, OneLoc			
		Reba (100)	100	506	51	32		245/85						755	81	220	160	TwistLoc, OneLoc			
		NEW SEKTOR (120)	80/100/120	533	51	32		265/85						770	81	220	160	TwistLoc, OneLoc			
		Recon RL (120)	80/100/120	530	51	32		265/85						760	81	220	160	TwistLoc, OneLoc			
		Judy Gold	80/100/120	530	51	30		265/85						770	81	220	160	TwistLoc, OneLoc			
		Judy Silver	80/100/120	530	51	30		265/85						770	81	220	160	PopLoc			
	Trail	Revelation	120/130/140/150	561	42/51	35		245/85						770	81	220	180	TwistLoc, OneLoc			
		Reba (150)	130/140/150	556	51	32		265/85						760	81	220	160	TwistLoc, OneLoc			
		Reba (120)	110/120	531	51	32		265/85						760	81	220	160	TwistLoc, OneLoc			
		NEW SEKTOR (150)	130/140/150	563	51	32		265/85						770	81	220	160	TwistLoc, OneLoc			
		Recon RL (140)	130/140	550	51	32		265/85						760	81	220	160	TwistLoc, OneLoc			
	Enduro	Lyrik	150/160/170/180	592	42/51	35		265/85						770	81	220	180	TwistLoc, OneLoc			
		Pike	120/130/140/150	561	42/51	35		245/85						770	81	220	180	TwistLoc, OneLoc			
		Yari	150/160/170/180	591	42/51	35		265/85						770	81	220	180	TwistLoc, OneLoc			
	Gravity	NEW BoXXer	180/190/200	602	56	35	268							770	81	220	200	Crown only			
29"+	Enduro	Pike	100/110/120/130/140/150/160	583	51	35		265/85						786	82	220	160	Crown only			
		Yari	100/110/120/130/140/150/160	583	51	35		265/85						786	82	220	160	Crown only			
700c	Urban	Paragon Gold	50/65	477	46	30	265 317 (XL)	265/85	QR					716	45	180	160	TwistLoc, OneLoc	X	Post	Dynamo hub/standard & proprietary light mount
		Paragon Silver	50/65	477	46	30	265 317 (XL)	265/85	QR					716	45	180	160	PopLoc	X	Post	

*All measurements in MM

MY19 ROCKSHOX REAR SUSPENSION TECHNICAL SPECIFICATION OVERVIEW

Metric Shocks		Damper Adjustment	Stroke (Eye to Eye: Standard-Bearing / Trunnion)				
			35 (170 / 145)	37.5-45 (190/165)	47.5-55 (210/185)	57.5-65 (230/205)	67.5-75 (250/225)
XC, Trail, Enduro, Gravity	Deluxe R	Rebound	X	X	X	X	
	Deluxe RT	Rebound / 2 position Threshold (Open / Threshold)	X	X	X	X	
	Deluxe RL	Rebound / 2 position (Open / Lock)	X	X	X	X	
	Deluxe RT3	Rebound / 3 Position Compression (open - mid - firm Threshold)	X	X	X	X	
	Deluxe RL Remote	Rebound / 2 position cable remote (Open / Lock)	X	X	X	X	
	Super Deluxe R	Rebound		X	X	X	X
	Super Deluxe RC3	Rebound / 3 Position Compression (open - mid - firm Threshold)		X	X	X	
	Super Deluxe RCT	Rebound / Low Speed compression adjust / 2 position Threshold (Open / Threshold)		X	X	X	X
	Super Deluxe RT Remote	Rebound / 2 position cable remote (Open / Threshold)		X	X	X	X
	Super Deluxe RCWC	Rebound / Low Speed compression adjust					X
	Super Deluxe Coil R	Rebound			X	X	X
	Super Deluxe Coil RCT	Rebound / Low Speed compression adjust / 2 position Threshold (Open / Threshold)			X	X	X
	Super Deluxe Coil RT Remote	Rebound / 2 position cable remote (Open / Threshold)			X	X	X
	Super Deluxe Coil RCWC	Rebound / Low Speed compression adjust					X

Rear Suspension		Damper Adjustment	Eye To Eye / Travel											Air Can Options				
			152 x 32	165 x 38	184 x 44	190 x 51	200 x 51	200 x 57	216 x 63	222 x 66	222 x 70	240 x 76	267 x 89	Standard Volume	High Volume	High Volume Eyelet	DebonAir	DebonAir w/ High Volume Eyelet
XC, Trail, Enduro	Monarch R	Rebound	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	Monarch RL	Rebound / 2 position (Open / Lock)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	Monarch RT	Rebound / 2 position Threshold (Open / Threshold)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	Monarch RT3	Rebound / 3 Position Compression (open - mid - firm Threshold)	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	Monarch Plus R	Rebound				X	X	X	X	X	X	X	X	X	X	X	X	X
	Monarch Plus RC3	Rebound / 3 Position Compression (open - mid - firm Threshold)				X	X	X	X	X	X	X	X	X	X	X	X	X
Gravity	Vivid	Low and High Speed Rebound / Low Speed compression adjust						X	X		X	X	X					
	Vivid Air	Low and High Speed Rebound / Low Speed compression adjust						X	X		X	X	X					

All dimensions are preliminary, and subject to change. Please check SRAM Connect.

**Option available through Line Extension Program