

取扱説明書

DRC ツーリングキャリア


CRF250L/L<S>/RALLY/RALLY<S> '21-,
CRF300L/L RALLY '21-

この度はDRC 商品をお買い上げいただき、誠にありがとうございます。
下記の内容をよくご覧になり正しく作業を行ってください。

1.注意事項

- 作業には専門の知識と技術が必要です。不用意に作業を行うと思わぬ事故や故障の原因となる場合があります。
- 定期的にボルトの緩みを確認して下さい。
※振動や衝撃により、取り付けが緩くなることがあります。
- 本製品の最大積載量は**5 kg**です。積載物の合計重量が積載制限以上にならないようにしてください。
- 既に車両に装着されている純正部品以外の製品、部品等によって本製品と干渉し使用できない場合があります。
- 製品に対し、加工・改造を行わないでください。
事故や破損の原因になります。

2.セット内容




セット内容

A.キャリア本体	1個
B.スペーサー1 (15mm)	2個
C.スペーサー2 (30mm)	2個
D.M8×45 キャップボルト	2個
E.M8×60 キャップボルト	2個


3.取り付け方法

- 1) フックボルトを4カ所共外します。(図1)
※純正のカラーはそのまま使用します。



- 2) キャリア本体 (A) を仮組していきます。(図2)

- 3) すべてのボルトを仮組後、本締めしていきます。
※仮組せずに取り付けしまうと、他の部分のボルトが取り付けできなくなる可能性があります。



Installation instructions

DRC TOURING CARRIER


CRF250L/L<S>/RALLY/RALLY<S> '21-,
CRF300L/L RALLY '21-

Thank you for purchasing this DRC product.
Please read these instructions carefully before installing.

1.Important notes

- Special knowledge and skills are required for installation. Careless work may cause an unexpected accident or failure.
- Check regularly for loose bolts.
*Installation may become loose due to vibration or impact.
- Maximum load on this product is **5 kg**. Please do not load luggage exceeding this limit.
- This product can not be used with other optional parts if they interfere with this product.
- Please do not modify this product.

2.Set Contents




Set Contents

A.Carrier	1ea
B.Spacer1(15mm)	2ea
C.Spacer2(30mm)	2ea
D.M8x45 Cap bolt	2ea
E.M8x60 Cap bolt	2ea

3.Installation

- 1) Remove the 4 hook bolts.(Fig 1)
*Please do not remove the collars.



- 2) Assemble the carrier without fully tightening the bolts.(Fig 2)

- 4) Once the carrier is correctly positioned and aligned, please fully tighten bolts.
*Without doing a temporary assembly to check installation, some bolts will not be able to be tightened.

